



Product Guide

FOA & FSA Series...

FSA & FOA Series

Residential and Light Commercial Unit Heaters



Flexible Offerings for Multiple Applications...

Introducing the FOA & FSA Series by ADP. These compact unit heaters provide solutions for all of your residential and light commercial heating needs.




Separated combustion uses a two pipe system to eliminate indoor contaminants from entering the heat exchanger compartment

FOA Series unit heaters only



Power exhaust system allows horizontal venting up to 25 feet



Easy to clean tubular heat exchangers, made of aluminized steel, provide resistance to corrosion and oxidation

Direct drive propeller fans are dynamically balanced for quiet and smooth operation





FSA Cayenne™ Series

Low Profile Unit Heaters



FOA Series

Separated Combustion Unit Heaters



FSA Series Application & Benefits:

- Residential - low profile units
- Great for garages & shops
- Wiring junction box is located inside of unit
- Self-diagnostic board with LED display improves troubleshooting
- 1" clearance from ceiling for easy installation

FOA Series Application & Benefits:

- Perfect for light commercial and green house applications
- Introduces clean combustible outside air when required
- Wiring junction box is located outside of unit

The ADP Advantage...

FLEXIBILITY

ADP provides solutions for all your residential and light commercial heating needs.

QUALITY

Every unit heater is run tested prior to shipping.

SERVICE

ADP unit heaters are made for seamless installation and easy access.

ENERGY

Natural gas and propane models available to meet your needs.

WARRANTY

FSA/FOA Series unit heaters feature a standard 2-years limited warranty on parts and 10-year limited warranty on aluminized heat exchanger.

FOA N 75

Series

FSA: Cayenne unit heaters
FOA: Separated combustion unit heaters

Gas

N: Natural gas
P: Propane

Nominal Gas Heat Input

FSA:
30, 45, 60, 75

FOA:
45, 100, 125, 150, 250, 300

Note: all unit heaters are 115V/1ph/60Hz

Recommended Sizing Guide	
UNIT	APPLICATION
FSA 30	1 to 1.5 car garage
FOA/FSA 45	2 to 2.5 car garage
FSA 60	3 to 3.5 car garage
FSA 75	uninsulated or larger detached garage

Mounting Clearance (in)	
Top	1
Bottom	0
Access side	18
Side	1
Back	18

FSA model size gas input (MBTUH)	30	45	60	75
Height (in)	12	12	17	17
Depth (in)	24	24	25	25
Width (in)	25	25	25	25
Flue connection size* (in)	3	3	4	4
Gas connections size NPT (in)	½	½	½	½

* diameter of round pipe - adaptor furnished with unit for flue connection

FOA model size gas input (MBTUH)	45	100	125	150**	250**	300**
Height (in)	12	21	21	27	39	39
Depth (in)	24	39 ⅝	39 ⅝	39 ⅝	39 ⅝	39 ⅝
Width (in)	26	36 ½	36 ½	36 ½	36 ½	36 ½
Flue connection size* (in)	3	5	5	5	5	6
Gas connections size NPT (in)	½	½	½	½	¾	¾

* diameter of round pipe - adaptor furnished with unit for flue connection
** sizes are not approved for residential application

Proudly distributed by:

2175 West Park Place Boulevard
Stone Mountain, Georgia 30087
www.adpnow.com

ISO 9001:2008
—Registered Quality System—



SL-FOA_FSA-07
February 2016