



## Gas Fired Unit Heater Cross Reference

Model Size (Input BUTH)	Power Vented 80% eff.								Separated Combustion 80% eff.								90+% eff.	
	Propeller				Blower				Propeller				Blower				Propeller	
	ADP	Modine	Reznor	Sterling	Modine	Reznor	Sterling		ADP	Modine	Reznor	Sterling	Modine	Reznor	Sterling	Modine	Reznor	
30	FSA*	HD	UDAP*	GG*	QVEF			UDBP										
45	FSA*	HD	UDAP*	GG*	QVEF			UDBP		FOA*	HDS	UDAS*	QVSF			UDBS		
60	FSA*	HD	UDAP*	GG*	QVEF	HDB		UDBP		FOA*	HDS	UDAS*	QVSF	HDC		UDBS		
75	FSA*	HD	UDAP*	GG*	QVEF	HDB		UDBP		FOA*	HDS	UDAS*	QVSF	HDC		UDBS		
90				GG*														
100	SEP	HD	UDAP*		QVEF	HDB		UDBP	QVEB	FOA*	HDS	UDAS*	QVSF	HDC		UDBS	QVSB	
105				GG*														
115	SEP																	
120				GG*														
125		HD	UDAP		QVEF	HDB		UDBP	QVEB	FOA*	HDS	UDAS*	QVSF	HDC		UDBS	QVSB	
130																	UEAS	
135																	PTC	
145	SEP																	
150		PDP	UDAP	TF	QVEF	BDP		UDBP	QVEB	FOA	PTS	UDAS	QVSF	BTS		UDBS	QVSB	
155																	PTC	
175	SEP	PDP	UDAP	TF	QVEF	BDP		UDBP	QVEB		PTS	UDAS	QVSF	BTS		UDBS	QVSB	
180																	PTC	
200	SEP	PDP	UDAP	TF	QVEF	BDP		UDBP	QVEB	FOA	PTS	UDAS	QVSF	BTS		UDBS	QVSB	
215																	PTC	
225			UDAP		QVEF			UDBP	QVEB			UDAS	QVSF			UDBS	QVSB	
230	SEP																	
250	SEP	PDP	UDAP	TF	QVEF	BDP		UDBP	QVEB	FOA	PTS	UDAS	QVSF	BTS		UDBS	QVSB	
260																	PTC	
300	SEP	PDP	UDAP	TF	QVEF	BDP		UDBP	QVEB	FOA	PTS	UDAS	QVSF	BTS		UDBS	QVSB	
310																	PTC	
345	SEP																	
350		PDP	UDAP	TF	QVEF	BDP		UDBP	QVEB		PTS	UDAS	QVSF	BTS		UDBS	QVSB	
400	SEP	PDP	UDAP	TF	QVEF	BDP		UDBP	QVEB		PTS	UDAS	QVSF	BTS		UDBS	QVSB	

Notes: \* Approved for residential applications.  
 ADP, Modine & Sterling (models GG & TF only) utilize a tubular heat exchanger.  
 Reznor (all models) & Sterling (models QVEF, QVSF, QVEB & QVSB) use a clam shell heat exchanger.