

## BOSS<sub>®</sub>



# BOSS® makes FireStop for UVAC/R simple!



#### **BOSS**<sub>®</sub> 136 Fireblock/Draftstop Sealant

Residential Construction

A noncombustible sealant for use as a filler in a nonrated construction where a fire and smoke seal is required.

Tested to UL 136 (ASTM E-136). Meets IRC, UBC, CABO, BOCA (NBC) 602.7, Item 4, 1995 edition

Color: Red

Availability: Standard cartridge, 20 oz. sausage,

28 oz. contractor cartridge



#### **BOSS**® 816 Intumescent FireStop Sealant

Residential & Commercial

An intumescent sealant with excellent resistance to vibration, designed for penetration sealing around pipes and ducts.

Not for use around fire dampers. Listed & Tested to UL 1479

(ASTM E-814). Meets IRC, UBC, CABO, BOCA (NBC), IBC.

Color: Red

**Availability:** Standard cartridge, 20 oz. sausage, 28 oz. contractor cartridge, 4.5 gallon pail



### BOSS® 760 Silicone FireStop Sealant

Residential & Commerci

Neutral cure silicone that sustains constant vibration, excellent for perimeter sealing around fire dampers. Will not intumesce.

Listed & Tested to UL 1479 (ASTM E-814). Meets IRC, UBC, CABO, BOCA

(NBC), IBC.

Color: Red

**Availability:** Standard cartridge, 20 oz. sausage,

28 oz. contractor cartridge



#### **BOSS**® 350 Fire Retardant Duct Sealant

osidential & Commercial

Duct sealant designed for use in low, medium and high velocity HVAC Duct Systems. Prevents air leakage and remains flexible at low and high temperatures.

Tested to UL 723 (ASTM E-84).

Color: Gray

Availability: Standard cartridge

For all BOSS® UL Tested Systems, please request our FireStop Catalog on CD or visit our website for a free download: www.bossproducts.com

Call the **BOSS**® 800-928-2677

Accumetric, LLC®

350 Ring Road • Elizabethtown, KY 42701

(270)769-3385 • 800-928-2677 • Fax: (270)765-2412

www.bossproducts.com

HVAC / 040912 BOSS is a registered trademark of Accumetric, LLC



## BOSS® PRODUCTS



# The BOSS® HVAC/R Advantage!

**BOSS**® **PRODUCTS** manufactures market specific, professional grade adhesives and sealants that enable you to increase your margin with your core customers.

- Not sold in Big Box
- VOC compliant products for "Green" conscious users
- 24 hour shipments
- Privately held US company located in Kentucky
- Marketing materials for all distributors and wholesalers
- Experienced sales force
- Technical support department
- Vast product line

"We help our distributors and wholesalers build a bigger invoice."

#### Established in 1970

In-house Research and Development Lab

Full Time Technical Sales Department available for On-site Consultation

200,000 sq. ft. Manufacturing and Packaging Facility

ISO 9001 Certified Manufacturer

WE DEVELOP IT. WE MAKE IT. WE CERTIFY IT!

Call the **BOSS**<sub>®</sub> 800-928-BOSS

Accumetric, LLC®

350 Ring Road • Elizabethtown, KY 42701

(270)769-3385 • 800-928-2677 • Fax: (270)765-2412

www.bossproducts.com







#### **HVAC/R Products**

#### **BOSS**® 312 NSF/FDA RTV Silicone Adhesive/Sealant

A paste like, one component acetoxy silicone adhesive/sealant that cures to a tough, rubbery solid when exposed to moisture in the air.

- Will not shrink, sag, slump or run off
- Excellent in overhead & vertical joints

Temp Range: -65°F to 400°F

Federal Specs: TT-S-00230C; TT-S-001543A; ASTM C-920; FDA 21-CFR 177.2600; NSF 51;

**UL** Recognized

31200 Clear / 31201 White / 31202 Black / 31203 Aluminum

31270 Clear / 31271 White / 31272 Black / 31273 Aluminum



#### **BOSS**® 370 HVAC/R RTV Silicone Adhesive/Sealant

A paste like, one component acetoxy silicone adhesive/sealant that cures to a tough, rubbery solid when exposed to moisture in the air.

- Seal heating, ventilating or air conditioning duct work
- Seal cracks and gaps around ducts, pipes, vents and fixtures

Temp Range: -65°F to 400°F continuous Federal Specs: TT-S-00230C; TT-S-001543A; ASTM C-920

Cartridge

37000 Clear / 37001 White / 37002 Black / 37003 Aluminum



Provides a protective coating or gasket where parts must perform at temperatures up to 500°F.

- · Used in critical bonding, sealing, potting and encapsulating applications
- Excellent resistance to weather, temperature extremes, and caustic environments

Temp Range: -85°F to 500°F Federal Specs: TT-S-00230C; TT-S-001543A; ASTM C-920; NSF 51; UL Recognized

32603-3 Oz. Cartridge



37 Sillicone

#### **BOSS**® 368 Butyl Rubber Adhesive/Sealant

A one component skinning product for sealing standing seam roofs, flashings and side walls. Provides excellent adhesion to metal, asphalt, wood and masonry substrates.

- · Filling cracks and joints around HVAC ducts, pipes and vents
- Excellent in sealing joints in sheet metal
- Compatible with and suitable for use on polyurethane foam and extruded polystyrene

Federal Specs: TT-S-001657; TT-C-1796A, Type I, Class A. Meets FDA Regulation, food additives, sub-part F, sub-paragraph 175.105 being composed of ingredients acceptable for packing and transporting food. BOSS® 368 is acceptable to the U.S. Department of Agriculture for use in meat and poultry processing areas under Federal Inspection.

36801 White / 36802 Black / 36803 Grey

#### **BOSS**® 333 Triple Expanding Foam

A ready to use, multi-purpose, polyurethane foam that expands to three times its original volume upon contact with air.

- · Use for insulating around pipes, cables and blank openings, gaps and cracks
- Weatherproofs against wind and moisture
- · Can be cut, sanded and painted

Temp Range: -200°F to 200°F R-Value: 4 to 5 per inch

Specs: ASTM E-84; UL 723: Flame Spread-15, Smoke Developed-15 Aerosol Can - 33316-12 Fl. Oz. / 33324-24 Fl. Oz.



#### **BOSS**® 362 100% Acrylic Tub 'N' Tile Caulk

This was developed for use around showers, tubs, tiles, toilets, backsplashes and sinks as well as baseboards, door frames, crown moulding and any joint where a watertight seal is needed.

- · Low temperature flexibility
- Paintable, mildew resistant, non-vellowing
- · Colors: clear, white, almond, biscuit/bone
- · Soap and water clean up before cure

#### Tube-5.5 Oz.

36250 Clear / 36251 Bright White / 36255 Almond / 36273 Biscuit/Bone

#### **BOSS**® 125 Multi-Seal

A one component, moisture curing sealant formulated to produce a flexible joint with excellent adhesion to many building materials including Kynar 500®, coated metals, glass, EIFS, galvanized steel, roofs, flashings, vents, downspouts, gutters, tiles and concrete. Suited to sealing construction joints in concrete structures, masonry joints, balcony and parapet joints, window and door perimeter joints, façade and metal cladding joints, ceramic tile joints, shop fronts and aluminum angle joints. Forms a strong bond even on damp surfaces. This VOC Compliant sealant is paintable with most latex paints\*. Best if painted within 7 days.

\*Test small area for compatibility before painting. Kynar 500® is a trademark of Arkema Inc.

12500 Clear / 12501 White / 12502 Black / 12503 Grey / 12507 Limestone 12513 Aluminum Grey / 12514 Hunter Green / 12515 Medium Bronze 12516 Off white / 12517 Redwood Tan / 12518 Stone / 12519 Tan 12520 Special Bronze / 12521 Brown

#### **BOSS**® 891 Hand Cleaner with Lanolin

Specially formulated to quickly and easily remove oil, grease, grime and stains without damaging the skin.

- · Removes paints, grease, oil, dirt, adhesives and sealants
- Not harmful to skin, contains lanolin
- 12 bottles / case

**Inverted Bottle** 89100-15 Oz.

#### **BOSS**® 270 Pipe Thread Sealant

A high quality industrial grade thread sealing compound that is grit-free, slow drying, soft setting and non-hardening. Ensures leak proof joints in both metal and plastic piping. Permits low torque make-up and easy disassembly without harming threads or seals. May be used for thread connections on all metals, ABS, PVC, CPVC and nylon plastics.

**Brush Top Cans** 27004-1/2 Pint 27008-Pint

#### **BOSS**® 271 Pipe Thread Sealant with PTFE

A high quality industrial grade thread sealing compound that is grit-free and non-hardening. Ensures leak proof joints in both metal and plastic piping. Permits low torque make-up and easy disassembly without harming threads or seals. May be used for thread connections on all metals, ABS, PVC, CPVC, polypropylene and nylon plastics.

**Brush Top Cans** 27104-1/2 Pint 27108-Pint





BOSS

125

#### **BOSS**® 348 Construction/Multi-Purpose Adhesive

A premium quality, waterproof adhesive specially designed for the bonding and installation of all types of plastic foams and polystyrene. When used as directed it will not attack polystyrene or other plastic foams. Adhesive forms a "bridge" between the panel and the bonding surface with a strong yet flexible bond. It will not cause any staining, bleeding or blistering effect.



- Reduces sound transmission
- · Fast grab, sets up quickly
- VOC Compliant

Cartridge 34800 Light Tan



#### **BOSS**® 892/893/894 Industrial Hand Wipes Specially formulated hand wipes

designed to quickly and easily remove oil, grease, grime and stains without damaging the skin.

- · Removes marker ink, paints, grease, oil, dirt, adhesives and sealants
- Not harmful to skin

89200-100 Soft Cloth Wipes 89300-80 Dual Sided-Smooth/Abrasive Wipes 89400-72 Biodegradable Wipes



This spray combines a uniform misting spray pattern with super high solids to create a fast tacking and high bond strength.

- VOC Compliant
- Nonchlorinated
- · Great for adhering insulation board to duct work
- · Adheres well for placement of signs and instructions to your work

Aerosol Can 63512-12 Oz





Accumetric, LLC® 350 Ring Road Elizabethtown, Kentucky 42701 USA 800-928-BOSS(2677) TEL (270)769-3385 / FAX (270)765-2412

www.bossproducts.com

