

25, 50 & 75 Pint Models

DEHUMIDIFIERS

Three options for disposal of condensate



THE EXPERTS IN ROOM AIR CONDITIONING

FEATURES

Comfort & Convenience:

- Top-mount digital touch controls display room temperature & relative humidity level
- Set humidity level from 30% to 90% RH
- Low temperature operation to 41°F
- Removable condensate bucket with handle
- Washable, slide-out filter
- 24 hr. ON/OFF timer (timer must be set for each use-no memory)
- 2-speed fan
- Automatic defrost cycle
- Auto-restart
- Casters for easy mobility
- 6 ft. power cord

Energy Efficiency:

- ENERGY STAR® models
- Fan cycles off with the compressor

Up to 3 Drainage Options:

- Intuitive drain pump operation senses condensate levels and begins draining process as needed. Unit will continue operations after emptying without any manual reset. All models come with removable condensate bucket (up to 16 pts.)
- All models have continuous drainage outlet
- D50 & D70 models have builtin drain pump that can pump condensation vertically or horizontally up to a combined distance of 15 feet

Sleek, Clean Modern Design

 Non-louvered front panel has a clean, stylish appearance that doesn't accumulate unsightly dust, pet hair and other household debris.

ססחלח

Dehumidifier Sizing Guide

Dehumidifier capacity is usually measured in pints per 24 hours and is determined by two factors:

The size of the space that needs to be dehumidified, and the conditions that exist in the space before dehumidification. Use the chart below to estimate the capacity you are looking for.

Room Conditions	Small to mid-size space 100 - 1,000 sq. ft.	Mid-size to large space 1,000 - 2,000 sq. ft.
Damp Area feels damp and has a musty odor only in humid weather	D25 (25 pint)	D50 (50 pint)
Very Damp 🍐 🍐 Area always feels damp & has a musty odor & may exhibit damp spots on walls & floors	D50 (50 pint)	D50 (50 pint)
Wet b b b Area always feels and smells wet and the walls & floors sweat or seepage is present	D50 (50 pint)	D70 (70 pint)
Extremely Wet A A A A A A A A A A	D50 (50 pint)	D70 (70 pint)



Built-in drain pump on 50 pt. and 70 pt. models

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA)	Wall Outlet Appearance	Power Cord Length
All models	125V-15A	5-15P		6 FT.



*The rating is expressed in pints per 24 hour period at 80° F and 60% relative humidity. Dehumidifiers are tested using the ANSI/AHAM DH-1 standard.

**Energy Factor: The energy efficiency of dehumidifiers is measured by its energy factor, in liters of water removed per kilowatt-hour (kWh) of energy consumed or L/kWh. In general, a higher energy factor means a more efficient dehumidifier.

As an ENERGY STAR[®] partner, Friedrich Air Conditioning Co. has determined that the selected ENERGY STAR[®] models meet the ENERGY STAR[®] guidelines for energy efficiency. One year limited warranty on parts and labor; five years on the sealed refrigeration system.

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.



Friedrich Air Conditioning Co. | 10001 Reunion Place, Suite 500 | San Antonio, TX 78216 | 877.599.5665 | www.friedrich.com

SPECIFICATIONS

Model Number

Model Number	D25BNP	DOUBPA	D70BP
ENERGY STAR®	No	Yes	Yes
Dehumidification Capacity* (Pints/24 hrs)	25	50	70
Built-in Drain Pump	No	Yes	Yes
Drain Pump Hose (Length ft)	-	16' 9"	16' 9"
Control	Digital	Digital	Digital
Power	115V/60HZ	115V/60HZ	115V/60HZ
Current (Amps)	4.5	5.2	8.2
Watts	240	600	900
Energy Factor (EF), L/kWh**	1.85	2.0	2.0
Compressor Type	Rotary	Rotary	Rotary
Refrigerant Type/Charge amount (Oz)	R-134A/4.9 Oz.	R-410A / 8.8 Oz	R-410A / 10.9 Oz
Operating Temperature Range	41°F- 95°F	41°F- 90°F	41°F- 90°F
Bucket Capacity (Pints)	11.5 approximate	16.2 approximate	16.2 approximate
Easy Roll Casters	Yes, included	Yes-built in	Yes-built in
Dimensions (WxHxD)	13 1/4 x 21 1/2 x 9 1/2	15" x 23 1/4" x 12"	
Net/Shipping Weight	32/34	41.2/45.9	44.3/48.9
Carton Dimensions (WxHxD)	15 x 20 3/4 x 11 1/2	16 1/4" x 24 3/4" x 13 3/4"	

D25RNP