

# PlenumPlus™ Commercial Grade Condensate Pump

# DATA SHEET

## Model A3/A5



- ◆ UL 2043 Tested
- ◆ Plenum rated
- ◆ Easy wire access
- ◆ Rated for use with steam condensate
- ◆ Heavy duty construction

Hartell's PlenumPlus™ Commercial Grade Condensate Pump A3/A5 has been tested to, and yielded results that fell within the acceptable criteria of UL standard 2043, Third Edition, **“Fire test for heat and visible smoke release for discrete products and their accessories installed in air-handling spaces.”** The UL standard 2043 rating assures the PlenumPlus pump is an optimal choice for use in plenum spaces.

## When safety counts, you can rely on Hartell PlenumPlus™

### FEATURES:

- ◆ 1 Gallon, heavy-duty reservoir
- ◆ Max temperature 212°
- ◆ Includes auxiliary safety switch on all models
- ◆ Reversible reservoir allows installation flexibility
- ◆ 12 month warranty

**PLENUM  
RATED**



Model	Voltage	Lift / Feet	Lift						Max Lift	Dimensions			
			6'	12'	18'	24'	36'	48'		30'	Width	Length	Height
A3	115V 3.1A* 208/230V 1.1A 277V 1.0A	Gallons / hr	351	309	245	180	-	-	-	6"	12"	10.5"	11lb
		Lift / Meters	1.8 m	3.7 m	5.5 m	7.3 m	11 m	15 m	9 m	15.24 cm	30.48 cm	26.67 cm	5 kg
		Liters / hr	1329	1170	927	681	-	-	-				
A5	115V 6.0A* 208/230V 3.3A 380/460V 1.1A	Lift / Feet	6'	12'	18'	24'	36'	48'	60'	Dimensions			
		Gallons / hr	550	528	495	462	390	306	-	Width	Length	Height	Weight
		Lift / Meters	1.8 m	3.7 m	5.5 m	7.3 m	11 m	15 m	18m	6"	12"	10.5"	15lb
		Liters / hr	2082	1999	1874	1749	1476	1158	-	15.24 cm	30.48 cm	26.67 cm	6.8 kg

\* Not UL Component Recognized

Tel: 215.322.0730 • Fax: 800.322.5519 • [www.hartell.com](http://www.hartell.com) • [info@hartell.com](mailto:info@hartell.com)



# DATA SHEET

## PlenumPlus™ Commercial Grade Condensate Pump

Model A3/A5

**PLENUM  
RATED**

**CR** US

**1  
YEAR  
WARRANTY**

